



H 5429/2

H54292000

KPS

Descrizione completa

Specifiche di prodotto

- Articolo: H 5429/2
- Capacity \hat{A} : 40n - 100 \square ($\pm 3\%$ 5 digits)
- Protection category: CAT. IV - 600V
- ABC Tools code: 154292000
- Catalogue code: H 5429 2000
- Pack: 1
- Not sold separately: No
- Data Hold \hat{A} : Yes
- EANCODE: 8435394747101
- Frequenza: 5 - 5M ($\pm 0,5\%$ 2 digits)
- Frequency (unit): HERTZ
- Auto range function \hat{A} : Yes
- Min/Max function \hat{A} : No
- Shell \hat{A} : protettivo in gomma
- ABC TOOLS Catalog Page: [akeneo_connector/media_files/P/a/Pag_0758_9f91.pdf](#)
- Weight: 1 kg
- Pre-configured data output: No
- Overload protection \hat{A} : No
- Automatic range: No
- AC voltage current \hat{A} : 0,1 $\hat{1}$ / $\hat{4}$ - 10 ($\pm 0,8\%$ 2)
- AC current range (unit): AMPERE



- DC voltage current \hat{A} : 0,1 $\hat{1}\frac{1}{4}$ - 10 ($\pm 1.5\%$ 2)
- DC current range (unit): AMPERE
- AC voltage range \hat{A} : 0.1 m - 400 ($\pm 0.8\%$ 5)
- AC voltage range (unit): VOLT
- DC voltage range \hat{A} : 0.1 m - 600 ($\pm 0.5\%$ 5)
- DC voltage range (unit): VOLT
- Resistance \hat{A} : 0,1 - 40M ($\pm 1\%$ 5)
- Resistance (unit): OHM
- LCD display resolution \hat{A} : 4000 punti
- Automatic switch-off: Yes
- Battery test \hat{A} : NO
- Continuity test \hat{A} : Yes
- Diode test \hat{A} : SI
- TTL logic test \hat{A} : No
- Packaging units: pcs.

