

**H 5433/7****H54337000****KPS**

## Descrizione completa

### Specifiche di prodotto

- Power supply: 1 x 6F22 9V
- Articolo: H 5433/7
- Capacity: 0.01 nF ÷ 6.6 nF (±4.0% 5 dig.) / 6.6 nF ÷ 660µF (±3.0% 3 dig.) / 660µF ÷ 66 mF (±4.0% 5 dig.)
- Protection category: CAT. III 1000V / CAT. IV 600V
- ABC Tools code: 154337000
- Catalogue code: H 5433 7000
- Pack: 1
- Not sold separately: No
- Data Hold: Yes
- EANCODE: 8435394747118
- Frequenza: 10 Hz ÷ 66 MHz (±1.5% 5 dig.)
- Frequency (unit): HERTZ
- Auto range function: Yes
- Min/Max function: No
- Shell: protettivo in gomma
- ABC TOOLS Catalog Page: [akeneo\\_connector/media\\_files/P/a/Pag\\_0758\\_6837.pdf](#)
- Weight: 0.406 kg
- Pre-configured data output: No
- Overload protection: No
- Automatic range: No



- AC voltage current  $\hat{A}$  : 1  $\mu$ A  $\div$  660 mA ( $\pm$ 1.5% 5 dig.) / 660 mA  $\div$  10 A ( $\pm$ 3.0% 5 dig.)
- AC current range (unit): AMPERE
- DC voltage current  $\hat{A}$  : 1  $\mu$ A  $\div$  660 mA ( $\pm$ 1.0% 5 dig.) / 660 mA  $\div$  10 A ( $\pm$ 2.0% 5 dig.)
- DC current range (unit): AMPERE
- AC voltage range  $\hat{A}$  : 1 mV  $\div$  660mV ( $\pm$ 1.5% 5 dig.) / 660mV  $\div$  660 V ( $\pm$ 1.2% 5 dig.) / 660V  $\div$  1000 V ( $\pm$ 1.0% 3 dig.)
- AC voltage range (unit): VOLT
- DC voltage range  $\hat{A}$  : 1 mV  $\div$  660mV ( $\pm$ 0.8% 3 dig.) / 660mV  $\div$  1000 V ( $\pm$ 0.5% 5 dig.)
- DC voltage range (unit): VOLT
- Resistance  $\hat{A}$  : 1k ( $\pm$ 0,8% 5 digits)
- Resistance (unit): OHM
- LCD display resolution  $\hat{A}$  : 6600 punti
- Automatic switch-off: Yes
- Continuity test  $\hat{A}$  : Yes
- Diode test  $\hat{A}$  : 3.2 V
- TTL logic test  $\hat{A}$  : No
- Packaging units: pcs.

