


In acciaio da bonifica - Tornite

Esecuzione brunita e fosfatata

In confezione indivisibile



Tipo piano - DIN 6340

Per bulloni	M	6	8	10	12	14	16	18	20	22	24	27	30
Codice	G 3752	0006	0008	0010	0012	0014	0016	0018	0020	0022	0024	0027	0030
G 3752/0	Cad. €												
Diametro foro D	mm	6,6	8,4	10,5	13	15	17	19	21	23	25	28	31
Diametro esterno d ₁	mm	17	23	28	35	40	45	45	50	50	60	65	68
Spessore h	mm	3,5	4	4	5	5	6	6	6	8	8	10	10
	pz.	10	10	10	10	10	10	10	10	10	10	1	1



Tipo convesso - DIN 6319 C

Per bulloni	M	6	8	10	12	14	16	20	24
Codice	G 3752	2006	2008	2010	2012	2014	2016	2020	2024
G 3752/2	Cad. €								
Diametro foro D	mm	6,4	8,4	10,5	13	15	17	21	25
Diametro esterno d ₁	mm	12	17	21	24	28	30	36	44
Spessore h	mm	2,3	3,2	4	4,6	5	5,3	6,3	8,2
Raggio		9	12	15	17	22	22	27	32
	pz.	10	10	10	10	10	10	10	10



Tipo concavo - 120°

DIN 6319 D

Per bulloni	M	6	8	10	12	14	16	20	24
Codice	G 3752	4006	4008	4010	4012	4014	4016	4020	4024
G 3752/4	Cad. €								
Diametro foro D	mm	7,1	9,6	12	14,2	16,5	19	23,2	28
Diametro esterno d ₁	mm	12	17	21	24	28	30	36	44
Spessore h	mm	2,8	3,5	4,2	5	5,6	6,2	7,5	9,5
	pz.	10	10	10	10	10	10	10	10



DIN 6319 G - Con diametro maggiorato e forte spessore

Per bulloni	M	6	8	10	12	14	16	20	24
Codice	G 3752	6006	6008	6010	6012	6014	6016	6020	6024
G 3752/6	Cad. €								
Diametro foro D	mm	7,1	9,6	12	14,2	16,5	19	23,2	28
Diametro esterno d ₁	mm	17	23	28	35	40	45	50	60
Spessore h	mm	4	4	5	5	5	6	8	10
	pz.	10	10	10	10	10	10	1	1



In acciaio da bonifica

Assortimenti **composti da 66 elementi** più utilizzati per il serraggio rapido e lo staffaggio:

- staffe diritte, a gradini, appoggi a gradino, tiranti filettati, viti testa a martello, dadi a T, dadi esagonali, manicotti di giunzione e rondelle piane

Forniti in cassetta

Per cava "a"	mm	12		14		16		18	
Codice		G 3753 0012		G 3753 0014		G 3753 0016		G 3753 0018	
G 3753	Cad. €								
Composti da	pz.	Grandezza	pz.	Grandezza	pz.	Grandezza	pz.	Grandezza	
Staffe diritte G 3748/1	4	012	4	014	4	016	4	016	
Staffe a gradino G 3748/7	4	012	4	012	4	016	4	016	
App. a gradino G 3749/2	2	31	2	31	2	31	2	31	
	4	64	4	64	4	64	4	64	
Tiranti filettati G 3751/2	2	10x80	2	12x80	2	14x100	2	16x125	
	2	10x100	2	12x160	2	14x160	2	16x160	
Viti testa a martello G 3751/3	2	12x80	2	14x100	4	16x100	4	18x150	
	4	12x125	4	14x150	2	16x150	2	18x200	
Dadi a T G 3751/4	4	10	4	12	4	14	4	16	
Dadi esagonali G 3751/7	12	12	12	14	12	16	12	18	
Dadi esagonali bassi	M	4	10	4	12	4	14	4	16
Manicotti di giunz. G 3751/9	4	10	4	12	4	14	4	16	
Rondelle normali foro D	4	10,5	4	13	4	15	4	17	
	12	13	12	15	12	17	12	19	
Cassetta LxPxh	mm	370x320x40		370x320x40		470x330x50		470x330x50	
Peso	kg	10,5		12		17		18	



G 3753 gr. 12



G 3753 gr. 16